

Intelligent Automation Incorporated

Coherent distributed radar for high-resolution through-wall imaging

SBIR Phase I Progress Report 9

Contract No. N00014-10-C-0277

Sponsored by

Office of Naval Research
COTR/TPOC: Martin Kruger



Prepared by
Eric van Doorn, Ph.D. (PI)
Satya Ponnaluri, Ph.D.

Distribution Statement A: Approved for public release; distribution unlimited.

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE JAN 2011		2. REPORT TYPE		3. DATES COVERED	
4. TITLE AND SUBTITLE Coherent Distributed Radar For high-resolution Through-Wall Imaging				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Intelligent Automation Incorporated, 15400 Calhoun Drive, Suite 400, Rockville, MD, 20855				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES The original document contains color images.					
14. ABSTRACT In this period of performance, we finalized the concept for the final demonstration. We have also demonstrated bench top frequency synchronization through our RF frontend.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES 3	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Summary

In this period of performance, we finalized the concept for the final demonstration. We have also demonstrated bench top frequency synchronization through our RF frontend.

1.0 INTRODUCTION

In this report we discuss progress in hardware design, synchronization algorithm, and definition of the final demonstration.

1.1 Synchronization algorithm

For frequency synchronization, we have completed a bench test of frequency synchronization through the RF front end and a wired attenuating channel.

1.2 Hardware design

We have constructed two complete synchronization transceivers (without antennas). We have determined the noise floor of the receiver. We have selected antennas.

1.3 Preparation for final demonstration

We have further developed the final demonstration scenario. We show the demonstration scenario in Figure 1 below. We will demonstrate a bi-static through-wall radar system. Bi-static radar, while more complex and harder to deploy than traditional monostatic radar, offers covert operation of the receiver, and increased resilience to electronic countermeasures as receiver location are potentially unknown as well as possible enhanced radar cross section of the target due to geometrical effects. For our final demonstration we propose a stationary transmitter, a mobile receiver, and a GPS base station. To be able to form SAR images from the received radar scattering, positions of both transmit and receive nodes must be known and both nodes must be synchronized, to within a small fraction of the transmitted bandwidth.

The stationary node consists of a synchronization transceiver, and a radar transmitter. It will be placed at a location with excellent GPS reception within 100m of the building. The radar transmitter will transmit radar pulses with timing derived from the synchronization transceiver. The radar frequency band will be sufficiently low to penetrate the building wall, with bandwidth in the one- to several hundred MHz. For the demonstration, we will use either a signal generator with modulation derived from the synchronization receiver, or a waveform directly synthesized by the same hardware used for the synchronization transceiver.

The mobile node consists of a synchronization transceiver, a radar receiver, a differential, dual band high-precision GPS receiver, and a PC. The mobile node will move along a trajectory near the building that will allow accurate GPS-aided positioning, and detection of radar reflections from the inside of the building. A directional antenna will be used and aimed by the user at the building. Its azimuthal orientation will be tracked and recorded with a magnetic compass. The accuracy of the synchronization will correspond to a small fraction of the radar signal bandwidth. The data corresponding to the received radar scans, timestamps from the synchronization transceiver, orientation of the radar antenna and the GPS location will be transferred to the PC, and processed in to a SAR image in semi-real time.

The GPS base station is located on the roof of the IAI office. It will provide corrections to the mobile GPS receiver.

We will use sufficiently stable clocks for the radar nodes so that the synchronization link can operate at very low duty cycle (<1 signal exchange /minute). Hence, the mobile radar node is largely passive.




Figure 1. Final Demonstration Scenario.

3.0 CONCLUSIONS AND WORK PLANNED FOR NEXT REPORTING PERIOD

The next reporting period will focus on implementation of the time offset estimation algorithm in the digital hardware, further characterization and testing of the RF hardware, specifically the ability to accurately measure hardware delays. We will complete the definition of the final demonstration and present a schedule of activities remaining in preparation for the demonstration.

3.0 REFERENCES

None.

4.0 LIST OF SYMBOLS, ABBREVIATIONS, AND ACRONYMS